



CEPILLO CIRCULAR TRENZADO

CLAVE	D		A		E		DIAMETRO DE ALAMBRE		SECCIONES
	mm	pulg	mm	pulg	mm	pulg	mm	pulg.	
I00301	152	(6")	20	(25/32")	15.8	(5/8")	0.35	0.014	1 SECC.
I00302	204	(8")	20	(25/32")	15.8	(5/8")	0.35	0.014	1 SECC.
I00320	102	(4")	18	(23/32")	15.8	(5/8")	0.35	0.014	1 SECC.
I00401	152	(6")	18	(23/32")	15.8	(5/8")	0.51	0.020	1 SECC.
I00402	204	(8")	18	(23/32")	15.8	(5/8")	0.51	0.020	1 SECC.
I00421	204	(8")	20	(25/32")	15.8	(5/8")	0.51	0.020	1 SECC.
I005620	COPA TRENZADO MULTIROSCA						0.35	0.014	1 SECC.

Aplicación: cardado de piezas de acero en superficies planas y/o anguladas trabajo pesado.



I00302



I00301

Cardas para:



Pulidora manual


ENTRADA MILIMETRICA (BOSH)

CLAVE	D		DIAMETRO DE ALAMBRE		E	
	mm	pulg	mm	pulg	mm	pulg
I01320	101.6	(4")	0.35	0.014	14	(9/16")

Aplicación: cardado de piezas de acero en superficies planas y/o anguladas trabajo pesado.



I01320



I00421